

markilux® RS 8000

The Sturdy Support Frame for Large Conservatory Awnings

markilux® RS 8000 (frame system)

The sturdy support for sunshades with a large surface area



Overall view



Wall fixture up to an angle of 30° is possible



Foot plate with upright inserted



Coupled awning with top and bottom coverboards



Coverboard and coupling plate

- easily fitted
- designed especially for the markilux® 8000
- profiles and connections designed for use in a building block system
- frame system made of extruded aluminium profiles
- can be supplied in the standard white and brown colours as well as in special RAL colours
- extensions up to 700cm are possible
- suitable for coupled awnings up to three fields wide
- as an optional extra (surcharge) top and bottom coverboards can be supplied


We reserve the right to make alterations without giving prior notice.



markilux® RS 8000

(Frame System)



Single Unit		Fixure width + 6 cm = overall width											
Dimensions	Fixture/order width in cm.	150	200	250	300	350	400	450	500 ¹⁾	550	600	650	
	Overall width ²⁾	156	206	256	306	356	406	456	506	556	606	656	
	Extension 150 cm.												
	Extension 200 cm.												
	Extension 250 cm.												
	Extension 300 cm.												
	Extension 350 cm.											3)	
	Extension 400 cm.								3)	3)	3)	3)	
	Extension 450 cm.								3)	3)	–	–	
	Extension 500 cm.								3)	–	–	–	
	Extension 550 cm.								–	–	–	–	
	Extension 600 cm.								–	–	–	–	
	Extension 650 cm.								–	–	–	–	
	Extension 700 cm.								–	–	–	–	
Additional field		Fixt. width single field + fixt. width additional field + 6 cm = overall width											
Available Accessories	Fixture/order width in cm.	150	200	250	300	350	400	450	500 ¹⁾	550	600	650	
	Extension 150 cm.												
	Extension 200 cm.												
	Extension 250 cm.												
	Extension 300 cm.												
	Extension 350 cm.											3)	
	Extension 400 cm.								3)	3)	3)	3)	
	Extension 450 cm.								3)	3)	–	–	
	Extension 500 cm.								3)	–	–	–	
	Extension 550 cm.								–	–	–	–	
	Extension 600 cm.								–	–	–	–	
	Extension 650 cm.								–	–	–	–	
	Extension 700 cm.								–	–	–	–	
Frame polyester powder coated as standard in colour *													

- 1) The cassette must be supported by an additional wall bracket in the middle from a width of 451 cm.
- 2) The overall width is that of the profiles if the brackets are fitted on the inside. Dimensions are given without top and bottom gutters.
- 3) These sizes are supplied with an additional transom to facilitate support of the cover support tube.

* white RAL 9016, brown RAL 8019
Other RAL colours are possible:
Availability and lead times on request.

N.B. Measure up carefully! We will not take awnings back because of incorrect size. Awnings are made to measure. Tolerances should be allowed for.
Please consult the special notes contained in the general information/markilux® fabric collections.
We reserve the right to make alterations without giving prior notice.